



WAVE REPORT FOR LONG BEACH (2019)

Deployment ID: DG009

Prepared By	Date	Version	Contact
Danielle Dempsey	January 2026	V2	P: 1-902-442-4660
Kiersten Watson			E: info@cmar.ca
Nicole Torrie			W: www.cmar.ca
Rachel Woodside			

Table of Contents

1 Introduction	3
1.1 Data Collection	4
1.2 Wave Parameters	5
1.3 Quality Control	6
2 DG009 Wave Data	7
2.1 Wave Variables	8
2.1.1 Time Series	8
2.1.2 Frequency	9
2.1.3 Wave Rose	10
2.2 Current	11
2.3 Depth	11
3 Data Acknowledgement	12
4 Document History	12
References	12

1 Introduction

The Centre for Marine Applied Research (CMAR) measures [essential ocean variables](#) around the coast of Nova Scotia through the Coastal Monitoring Program. As a part of this Program, the Nova Scotia Department of Fisheries and Aquaculture (NSDFA) and CMAR have deployed Acoustic Doppler Current Profilers (ADCPs) to measure sea state (waves) and currents. This document presents deployment details and summary figures of sea state data collected for a deployment in Digby County (Figure 1), at the **Long Beach** Station (Figure 2) in 2019 (deployment ID DG009). The corresponding current report can be found on the [Reports page](#) of the CMAR website.

The data are available for download from the Nova Scotia [Open Data Portal](#). For more information on CMAR and the sea state datasets, visit the [CMAR website](#).

This document should be considered as a guide only, as data collection is ongoing. The information may be revised pending ongoing data collection and analyses.




Figure 1: Digby County (green).




Figure 2: Location of ADCP deployed at the Long Beach station in St. Marys Bay in 2019.

1.1 Data Collection

NSDFA collects wave data using upward facing ADCPs that are mounted on the sea floor for 1 - 3 months (Figure 3). An ADCP uses sound to measure current speed and direction through the water column. ADCP data processing software uses many measurements over a given time interval to calculate key sea state parameters, including wave height, period, and direction (RD Instruments, 2017).

NSDFA uses several ADCP instrument models, including the Sentinel V20, Sentinel V50, Sentinel V100, and Workhorse Sentinel 600kHz. NSDFA processes the data using Velocity and WavesMon4 Software (Teledyne RD Instruments, 2017), and sends the output to CMAR. CMAR compiles and formats the data for publication with the [waves](#) R package (Dempsey & Torrie, 2024).

For an overview of “Waves Basics” and the wave calculations made by the Velocity and WavesMon software, refer to RD Instruments (2001). For more details on the instruments and software, refer to RD Instruments (2017) and Teledyne RD Instruments (2017).



Figure 3: Schematic representation of ADCP deployment (not to scale).

1.2 Wave Parameters

Wave variables derived from the power spectra are presented here and published in the corresponding dataset. The variables derived from the zero-up crossing analysis (average height of the largest one-third and one-tenth of waves, maximum wave height, and their corresponding periods) are not included. These variables are less reliable than the power spectra variables, especially during calm conditions (Teledyne RD Instruments, 2017).

Wave height is the vertical distance between the peak and trough of a wave (RD Instruments, 2017). One of the most common wave height parameters is the significant wave height, which is four times the square root of the zeroth-order moment of the wave spectrum (RD Instruments, 2017). This roughly corresponds to the average height of the largest one-third of waves in the sampling interval (RD Instruments, 2017).

Wave period is the time between consecutive waves. The peak wave period is associated with the largest spike of the power spectrum for a given time interval (Teledyne RD Instruments, 2017). Peak wave direction indicates the direction the peak wave energy is propagating from (RD Instruments, 2017). Direction is reported here relative to True North.

Peak period and peak direction observations may be less reliable when there is low wave energy (e.g., wave height < 0.5 m for a 600 kHz ADCP or 0.25 m for a 1000 kHz ADCP). When the sea is calm, the wave spectra are relatively flat and there may not be a clear peak from which to derive the period or direction value. This can result in large peak period values, erratic peak direction

values, and negative values. See the Quality Control section for detail on how these observations are treated for this report.

Significant wave height, peak period, and wave direction figures are presented below. The ADCP software also calculates the current speed and direction from three near-surface bins and the sensor depth below the surface. These variables are presented to provide additional context for the wave data.

In addition to wave variables presented in this report, the ADCP also measured current speed and direction throughout the water column. A report summarizing the full current speed and direction data at this location can be found on the [CMAR website](#). The corresponding Wave and Current datasets can be accessed through CMAR's [Data Access Map](#) or directly from the [Nova Scotia Open Data Portal](#).

1.3 Quality Control

The ADCP software automatically performs some Quality Control checks during data processing (RD Instruments, 2001; Teledyne RD Instruments, 2017). In addition, CMAR applied an automated Gross Range test to the processed data to identify outlying and unexpected values. For consistency with the CMAR Water Quality data, each data point was assigned a flag of "Pass", "Fail", or "Suspect/Of Interest"¹ (IOOS, 2020).

Observations flagged as "Pass" were within the expected range of the variable based on historical conditions. These observations are shown in the figures below. Observations flagged as "Fail" were outside of reasonable ranges for the variable, e.g., negative values or direction observations greater than 360 degrees. These observations are not shown in the figures.

Observations flagged as "Suspect/Of Interest" were statistical outliers and were reviewed by human experts. Significant wave height observations flagged as "Suspect/Of Interest" were typically recorded during extreme events like hurricanes. These are considered "Of Interest" and are included in the figures below. Peak period observations flagged as "Suspect/Of Interest" were typically recorded when there was low wave energy (e.g., flat power spectra). These observations were considered "Suspect" and not included in the figures below, since the ADCP software often cannot derive an accurate period value under calm conditions (Teledyne RD Instruments, 2017). Users should critically evaluate all period observations, especially during calm conditions.

The direction observations may also be unreliable during calm conditions. However, these observations will be flagged as "Pass" if they are within 0 to 360 degrees, since observations within this range are plausible. This may result in erratic direction time series, and users may prefer to apply additional Quality Control to these observations.

¹The "Not Evaluated" flag level is not applicable for the Gross Range test.

2 DG009 Wave Data

Table 1: DG009 deployment details.

Station	Long Beach
Instrument Model	Sentinel_V100
Latitude	44.41283
Longitude	-66.1466
Deployment Date	2019-01-17
Recovery Date	2019-03-01
Duration (d)	43
Depth Sounding (m)	30
Ensemble Interval (s)	600
Averaging Interval (s)	600
Pings per Ensemble	100
Sensor Height above Sea Floor (m)	0.6
First Bin Range (m)	3
Bin Size (m)	1

2.1 Wave Variables

2.1.1 Time Series




Figure 4: Wave variables over time. Top: significant wave height; Middle: peak period; Bottom: direction wave is travelling from.

2.1.2 Frequency




Figure 5: Histogram of wave variable observations. Top: significant wave height (bin width = 0.1 m); Middle: peak period (bin width = 2 seconds); Bottom: direction the wave is travelling from (bin width = 20 degrees).

2.1.3 Wave Rose




Figure 6: Wave height and the direction the wave is travelling from (relative to True North).

2.2 Current




Figure 7: Current speed and direction for three near-surface bins. Top: Current speed and the direction the current is travelling to (relative to True North). Bottom: Current speed distribution. The number of observations is noted above each bar.

2.3 Depth




Figure 8: ADCP sensor depth below the surface over time.

3 Data Acknowledgement

CMAR aims to prioritize data collection and processing efforts that best serve coastal stakeholders. If you use this Coastal Monitoring Program data in a project or for decision making, please complete our [anonymous questionnaire](#) with your feedback. Please cite the report and/or datasets used.

4 Document History

Version	Date	Amendments
V1	2025	New document.
V2	2026	Refreshed report template.

References

Dempsey, D., & Torrie, N. (2024). Waves: Format and visualize ADCP wave data. <https://github.com/dempsey-CMAR/waves>

IOOS. (2020). QARTOD Manual for Real-Time Oceanographic Data Quality Control Flags (1.2). https://cdn.ioos.noaa.gov/media/2020/07/QARTOD-Data-Flags-Manual_version1.2final.pdf

RD Instruments. (2001). Waves User's Guide (P/N 957-6148-00 (April 2001)). <https://www.commtec.com/prods/mfgs/RDI/Software/Manuals/Waves-Manual/Waves%20Users%20Guide.pdf>

RD Instruments. (2017). Waves Primer: Wave Measurements and the TRDI ADCP Waves Array Technique. https://www.teledynemarine.com/en-us/products/SiteAssets/RD%20Instruments/RDI_Waves_Primer.pdf

Teledyne RD Instruments. (2017). Velocity Software User's Guide (P/N 95D-6000-00 (January 2017)).